

ACE ROOF COATINGS, INC.

Safety Data Sheet DynaSHIELD® Dab-It

SECTION 1: Identification

Product identifier

Product name DynaSHIELD® Dab-It

Product number 7892010
Brand DynaSHIELD®

Recommended use of the chemical and restrictions on use

This is designed to be applied over both rusted and non-rusted metal fasteners to seal every fastener from water penetration.

Supplier's details

Name Ace Roof Coatings, Inc. Address 4821 Grisham Drive

Rowlett, TX 75088 United States

Telephone 972-864-0240 Fax 469-366-9219

email info@arcroofcoat.com

Emergency phone number(s) INFOTRAC - 800-535-5053

OUTSIDE UNITED STATES CALL COLLECT 1-352-323-3500

SECTION 2: Hazard identification

Classification of the substance or mixture

GHS classification in accordance with OSHA (29 CFR 1910.1200)

- Flammable liquids (chapter 2.6), Cat. 3
- Acute toxicity (chapter 3.1), Cat. 4
- Eye damage/irritation (chapter 3.3), Cat. 2A
- Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3
- Skin corrosion/irritation (chapter 3.2), Cat. 2
- Hazardous to the aquatic environment long-term hazard (chapter 4.1), Cat. 2
- Flammable liquids (chapter 2.6), Cat. 2

GHS label elements, including precautionary statements

Pictogram



Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapor H226 Flammable liquid and vapor

H312 Harmful in contact with skin H315 Causes skin irritation

H319 Causes serious eve irritation

H332 Harmful if inhaled

H335 May cause respiratory irritation May cause drowsiness or dizziness H336

H411 Toxic to aquatic life with long lasting effects

Precautionary statement(s)

Keep away from heat, hot surfaces, sparks, open flames, and other ignition P210

sources. No smoking.

P233 Keep container tightly closed.

Ground/bond container and receiving equipment. P240

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools. P242

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves/protective clothing/eye protection/face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P370+P378 In case of fire: Use foam, fog, dry chemical CO2, or water to extinguish.

P403+P235 Store in a well ventilated place. Keep cool.

Dispose of contents/container in accordance with Federal, State and local P501

regulations

P264 Wash any exposed skin thoroughly after handling.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention. P337+P313 Avoid breathing dust/fume/gas/mist/vapours/spray. P261 Use only outdoors or in a well-ventilated area. P271

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P403+P233 Store in a well ventilated place. Keep container tightly closed.

Store locked up. P405

P302+P352 IF ON SKIN: Wash with plenty of water/soap.

Specific treatment (see first aid instructions on this label). P321 P332+P313 If skin irritation occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.

Avoid release to the environment. P273

P391 Collect spillage.

Other hazards which do not result in classification

No data available.

Statement regarding ingredients of unknown toxicity (OSHA)

Not applicable.

SECTION 3: Composition/information on ingredients

Mixtures

Hazardous components

1. Component 1 (trade secret)

Concentration 20 - 25 % (Weight)

2. Calcium carbonate

Concentration 10 - 20 % (Weight)

CAS no. 471-34-1

3. TITANIUM DIOXIDE

Concentration 10 - 20 % (Weight)

CAS no. 13463-67-7

4. 1,2,4-Trimethylbenzene

 Concentration
 5 - 10 % (Weight)

 EC no.
 202-436-9

 CAS no.
 95-63-6

 Index no.
 601-043-00-3

- Flammable liquids (chapter 2.6), Cat. 3 - Acute toxicity (chapter 3.1), Cat. 4

- Eye damage/irritation (chapter 3.3), Cat. 2

- Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3

- Skin corrosion/irritation (chapter 3.2), Cat. 2

- Hazardous to the aquatic environment - long-term hazard (chapter 4.1), Cat. 2

H226 Flammable liquid and vapor

H315 Causes skin irritation

H319 Causes serious eye irritation

H332 Harmful if inhaled

H335 May cause respiratory irritation

H411 Toxic to aquatic life with long lasting effects

5. XYLENES (MIXED)

Concentration 10 - 20 % (Weight)

EC no. 215-535-7 CAS no. 1330-20-7 Index no. 601-022-00-9

- Flammable liquids (chapter 2.6), Cat. 3 - Acute toxicity (chapter 3.1), Cat. 4

- Skin corrosion/irritation (chapter 3.2), Cat. 2

H226 Flammable liquid and vapor H312 Harmful in contact with skin H315 Causes skin irritation

H332 Harmful if inhaled

6. ETHYLBENZENE

Concentration 10 - 20 % (Weight)

EC no. 202-849-4 CAS no. 100-41-4 Index no. 601-023-00-4

- Flammable liquids (chapter 2.6), Cat. 2 - Acute toxicity (chapter 3.1), Cat. 4

H225 Highly flammable liquid and vapor

H332 Harmful if inhaled

7. Component 7 (trade secret)

Concentration 10 - 15 % (Weight)

8. Silicon dioxide

Concentration 1 - 3 % (Weight) CAS no. 69012-64-2

9. Component 9 (trade secret)

Concentration 1 - 3 % (Weight)

Trade secret statement (OSHA 1910.1200(i))

Specific chemical identity and exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4: First-aid measures

Description of necessary first-aid measures

General advice In case of accident or if you feel unwell, seek medical advice IMMEDIATELY.

(Show the product label where possible)

If inhaled Remove victim from exposure to well-ventilated area. If breathing is

labored, qualified personnel should administer oxygen. Apply artificial respiration if breathing has ceased or shows signs of failing. Call a Physician.

In case of skin contact Remove contaminated clothing. Immediately wash affected areas

thoroughly with soap and water. If irritation, redness, or a burning sensation develops and persists, obtain medical advice. Contaminated clothing should

be thoroughly cleaned before reuse.

In case of eye contact Immediately flush eyes running water for a minimum of 15 minutes. Hold

eyelids open during flushing. If irritation persists, repeat flushing. Obtain

medical attention IMMEDIATELY.

If swallowed Do NOT induce vomiting. Provided the patient is conscious, wash out

mouth with water then give 1 or 2 glasses of water to drink. This material can enter lungs during swallowing or vomiting and cause lung inflammation and damage. Refer person to medical personnel for immediate attention.

Personal protective equipment for first-aid responders

None.

Most important symptoms/effects, acute and delayed

No data available.

Indication of immediate medical attention and special treatment needed, if necessary

No data available.

SECTION 5: Fire-fighting measures

Suitable extinguishing media

Use foam, fog, dry chemical CO2, or water.

Specific hazards arising from the chemical

Carbon oxides

Special protective actions for fire-fighters

As appropriate for surrounding materials/equipment. If electrical equipment is involved, the use of foam should be avoided. No unusual fire or explosion hazards.

Further information

No data available.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ventilate area.

Environmental precautions

In case of large spill, dike the area to prevent this material from entering water systems or sewers.

Methods and materials for containment and cleaning up

Absorb spill with an absorbent material such as sawdust, vermiculite or sand, and place in a closed container.

Reference to other sections

No data available.

SECTION 7: Handling and storage

Precautions for safe handling

Avoid open flames, electrical sparks or static electricity.

Conditions for safe storage, including any incompatibilities

Keep containers properly sealed and when stored indoors, in a well-ventilated area. Avoid storage above 110 °F

Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

Control parameters

1. Titanium dioxide - Total dust (CAS: 13463-67-7)

PEL (Inhalation): 15 mg/m3 (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

2. Titanium dioxide - Total dust (CAS: 13463-67-7)

PEL (Inhalation): See PNOR (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

3. Titanium dioxide - Total dust (CAS: 13463-67-7)

REL (Inhalation): Ca, (ultrafine particles), 2.4 mg/m3Ęfine), 0.3 mg/m3(ultrafine), See Appendix A, See Appendix C

(NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

4. Xylenes (o-, m-, p-isomers) (CAS: 1330-20-7)

PEL (Inhalation): 100 ppm (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

5. Xylenes (o-, m-, p-isomers) (CAS: 1330-20-7)

PEL (Inhalation): 435 mg/m3 (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

6. Xylenes (o-, m-, p-isomers) (CAS: 1330-20-7)

PEL (Inhalation): 100 ppm, (ST) 150 ppm, (C) 300 ppm (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

7. Xylenes (o-, m-, p-isomers) (CAS: 1330-20-7)

REL (Inhalation): 100 ppm, (ST) 150 ppm (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

8. Ethyl benzene (CAS: 100-41-4)

PEL (Inhalation): 100 ppm (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

9. Ethyl benzene (CAS: 100-41-4)

PEL (Inhalation): 435 mg/m3 (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

10. Ethyl benzene (CAS: 100-41-4)

PEL (Inhalation): 100 ppm, (ST) 125 ppm (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

11. Ethyl benzene (CAS: 100-41-4)

REL (Inhalation): 100 ppm, (ST) 125 ppm (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

Appropriate engineering controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV (s). General ventilation is recommended. Additional local exhaust ventilation is recommended where vapors, mists, or aerosols may be released. For guidance on engineering control measures refer to publications such as the ACGIH current edition of "Industrial Ventilation, a manual of Recommended Practice."

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Chemical splash goggles in compliance with OSHA regulations are advised. However, OSHA regulations also permit other types of safety glasses. (Consult your safety equipment supplier)

Skin protection

Wear protective clothing to prevent skin contact. Keep exposed skin area to a minimum. Protective clothing should be selected and used in accordance with "Guidelines for the Selection of Chemical Protective Clothing" published by ACGIH. Eye wash station and safety shower should be available.

Body protection

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

This product has demonstrated no observable effects at room temperature; however, it is highly recommended that an air-purifying respirator with organic filter cartridges be worn. In addition, in any interior, confined space, spray application, a supplied air source must be provided. When the product is sprayed or heated without adequate ventilation, an approved MSHA/NIOSH positive-pressure, supplied-air respirator may be required. Air purifying respirators equipped with organic vapor cartridges and a Hepa (P100) particulate filter may be used under certain conditions when a cartridge change-out schedule has been developed in accordance with the OSHA preparatory protection standard (29 CFR. 1910.134).

Thermal hazards

No data available.

Environmental exposure controls

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance/form

Odor

Odor threshold

рΗ

Melting point/freezing point

Initial boiling point and boiling range

Flash point Evaporation rate

Flammability (solid, gas)
Upper/lower flammability limits

Upper/lower explosive limits Vapor pressure

Vapor density Relative density

Solubility(ies)

Partition coefficient: n-octanol/water

Auto-ignition temperature Decomposition temperature

Viscosity

Explosive properties Oxidizing properties

Other safety information

No data available.

Thick yellow liquid Solvent odor No data available.

8.5 – 9.0 No data

313°F - 572°F (156°c - 300°C)

114°F .36

No data available.

No data 0.5% / 6.0%

2.9

Heavier than air

No data

Insoluble in water

No data No data No data Butter Grade No data No data

SECTION 10: Stability and reactivity

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None known.

Conditions to avoid

Avoid storage above 110°F.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition products

By fire: Carbon Dioxide, Carbon Monoxide

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

No information available.

Skin corrosion/irritation

Exposure causes skin irritation. Prolonged or repeated exposure may dry the skin. Symptoms may include redness, burning, drying and cracking. Skin absorption is possible, but harmful effects are not expected from this route of exposure under normal `conditions of handling and use

Serious eye damage/irritation

Exposure to liquid or vapor causes eye irritation. Symptoms may include stinging, tearing, redness and swelling.

Respiratory or skin sensitization

Short-term inhalation toxicity is low. Breathing small amounts during normal handling is not likely to cause harmful effects. Breathing large amounts may cause overexposure symptoms, such as headache, nausea, and irritation of nose and throat.

Germ cell mutagenicity

No information available.

Carcinogenicity

The ingredients of this product are not classified as carcinogenic by ACGIH or IARC, not regulated as carcinogens by OSDHA, and not listed as carcinogens by NTP.

Reproductive toxicity

No information available.

STOT-single exposure

No information available.

STOT-repeated exposure

No information available.

Aspiration hazard

No information available.

SECTION 12: Ecological information

Toxicity

No data available

SECTION 13: Disposal considerations

Disposal of the product

Liquid waste must be disposed of in accordance with Federal, State and local regulations. Incineration is the preferred method.

Disposal of contaminated packaging

Empty containers should be decontaminated and either passed to an approved drum recycler or destroyed.

Waste treatment

This product, as supplied, is regulated as a hazardous waste by the U.S. Environmental Protection Agency (EPA) under Resource Conservation and Recovery Act (RCRA) regulations. If discarded in its purchased form, this product is a RCRA hazardous waste. It is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or residue of the product remains classified a hazardous waste as per 40 CFR 261, Subpart C. State or local regulations may also apply if they differ from the federal regulation.

Sewage disposal

Chemical waste, even small quantities should never be poured down drains, sewers or waterways.

Other disposal recommendations

RCRA HAZARD CLASS: D001, Ignitable Hazardous Waste

SECTION 14: Transport information

DOT (US)

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

SECTION 15: Regulatory information

Safety, health and environmental regulations specific for the product in question

Toxic Substances Control Act (TSCA) Inventory

This material or its components are listed on the TSCA Chemical Substance Inventory and is in compliance with all applicable rules and orders. One or more of the components may be exempt from listing on the TSCA Inventory.

SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard, Fire Hazard

New Jersey Right To Know Components

Common name: ZINC CHROMATE

CAS number: 13530-65-9

Pennsylvania Right To Know Components

Chemical name: Chromic acid, zinc salt (1:1)

CAS number: 13530-65-9

California Prop. 65 components

Chemical name: Zinc chromate CAS number: 13530-65-9 02/27/1987 - Cancer

12/19/2008 - Developmental, female, male

Chemical Safety Assessment

No data available.

HMIS Rating

DynaSHIELD® Dab-It	
HEALTH	3
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	Χ

NFPA Rating



SECTION 16: Other information

CHANGES SINCE PREVIOUS SDS: GHS formatting changes.

Further information/disclaimer

This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.

Preparation information

Emily Mendel 05/28/2015