

A·R·C·HITECTURAL[®]

ROOF COATINGS



MADE IN  THE USA

● **PRODUCT DATA SHEET**

DynaSHIELD[®]

LO-ODOR STAIN BLOCKER

● **DESCRIPTION**

DynaSHIELD[®] Lo-Odor Stain Blocker is a proprietary blend of polymers. It is an oil-based product. DynaSHIELD[®] Lo-Odor Stain Blocker dries by evaporation, leaving a non-breathing, monolithic membrane that stops asphalt bleeding.

● **RECOMMENDED USES**

DynaSHIELD[®] Lo-Odor Stain Blocker is used as a blocker/sealer over asphalt products before the white finish coat is applied. Apply over all cured asphalt-based products.

● **APPLICATION**

Surface to be treated must be clean and dry. **Do NOT apply over moisture in or on roof deck.** For best results, apply with a sprayer at a rate of 1.5 gallons per roofing square and wait 24 hours before applying top coat. Apply evenly at a surface temperature of 35° F or greater. If there is bleed through after the first pass, apply another pass of DynaSHIELD[®] Lo-Odor Stain Blocker.

● **BENEFITS**

- Stops Asphalt Bleeding
- Cleans Easily
- Flexible
- Prevents Rust
- Waterproofs
- Freeze Resistant
- Nano-processed
- Low Odor

● **TECHNICAL DATA**

TENSILE:	1600 psi ASTM D-2370
ELONGATION:	250 % ASTM D-2370
COLOR:	Aluminum
PERMEABILITY:	Non-breathing ASTM E-1653
SOLIDS:	Weight 50% +/- 2% ASTM D-1353
SOLIDS:	Volume 37% +/- 2% ASTM D-2697
WEIGHT:	9.1 lbs. per gallon +/- 2%
VISCOSITY:	7,000 to 9,000 cps.
ABRASION:	Passed ASTM D-986
HARDNESS:	65 Shore A ASTM D-2240
STORAGE:	3 years unopened between 40° F - 100° F
DRY TIME:	1 hr. at 75° F and a thickness of 12 wet mils
FULL CURE:	24 - 72 hours depending on humidity, air movement, and temperature
CLEAN-UP:	Biodegradable citrus cleaning products or ARC's Cleaning Solvent for oil-based products
ADHESION:	Passed ASTM D-3359
PIGMENT:	Processed Metal
VOC:	<541 grams per liter

- *Avoid breathing fumes and prolonged contact with skin. Do not ingest. Keep containers covered when not in use. When using, provide proper ventilation. Dispose of product and container in accordance with local disposal codes.*

**CONSULT ARC TECHNICAL DEPARTMENT
FOR ANSWERS TO ANY QUESTIONS
REGARDING USE OF THIS PRODUCT**

System warranty available. When sold separate from system there is no warranty given, expressed or implied, through the values or statements made here, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by our in house and independent third party labs in order to obtain approval and/or classification. Acceptance, purchase and selection of these products are the sole responsibility of the buyer, buyer's agent, or the buyer's customer. ARC assumes no responsibility for coverage, performance, or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER GUARANTY OR WARRANTY OF ANY KIND IS MADE BY ACE ROOF COATINGS, INC. OR ITS SUBSIDIARIES, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING COSMETIC APPEARANCE, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.