

# A·R·C·HITECTURAL

## ROOF COATINGS



# ft G ACRYLIC PRIMER

### PRODUCT DATA SHEET

#### DESCRIPTION

ESP- "DSZMJD 1SJNFS JT B DPNCJOBUBJPO PG IJH/4S&EF QTJ "45. %  
 MBUYF BDSZMJDT JO XBUFS \*U ESJFT CZ FWBQP(\$5U)JPO UP B"DMF&S IJHI  
 MVTUFS TVSGBDF UIBU IBT FYDFQUJPOBM BC\$B-TUJ SF \$MIFBSCUFS (MPTT PQUJNB M  
 QSPEVDU EPFT OPU BMUFS UIF DPMP S PG UIF1 & Y.S&BDF5#S.FBUHUSFBUEF SNT ! NJM

#### RECOMMENDED USES

5IJT NBUFSJBM DBO CF VTFE BT B Q\$JNFS PWF\$ \$N#UBM NPEJGJDETT  
 TNPPUI #63 17\$ 510 )ZQBMPO &1%. FUD U#3"JODSFBTBTTFE "45. %  
 BEIFTJPO (%)&4\*0/ 1BTTFE "45. %

#### APPLICATION

4VSGBDF TIPVME CF DMFBO ESZ BOE TPVOE '6"MN6BYJTUJOPHST\$GBDFIVNJEJUZ PS M  
 EJPUMSFBTF BOE EFCSJT TIPVME CF SFNPWFES&F&G\$F #JPEFHSBEBCMF DJUSVT DMF  
 BQQMJDBQMPZOXJUI B CSVTI SPMMFS PS TQSBZFS %P OFPUBQ XJUI XBUFS  
 EJMVF PS BMUFS UIJT QSPEVDU "QQMZ BU7B\$BUBF PG HSBNTBOMFOMQVFS  
 TRVBSF GFFU' B"QEQNZTBOH

#### BENEFITS

"CSBTJPO 3FTJTUBOU  
 &BTZ \$MFBO 6Q  
 \$PTU 4BWJOHT  
 &BTF PG "QQMJDBUJPO  
 \*ODSFBTFE "EIFTJPO

#### TECHNICAL DATA

40-\*%4 8FJHIU "45. %  
 40-\*%4 7PMVNF "45. %  
 8&\*( )5 MCT QFS HBMMPO  
 U#3"JODSFBTBTTFE "45. %  
 (%)&4\*0/ 1BTTFE "45. %  
 )"3%/&44 4IPSF " "45. %  
 4503"(& ZFBS  
 %3: 5\*.& IPVVS BU i' BU B UIJDLOFTT

**CAUTION: High humidity requires a longer time for water-based coatings to form a film that is rain resistant.**

Avoid breathing fumes and prolonged contact with skin. Do not ingest. Keep containers covered when not in use. When using, provide proper ventilation. Dispose of product and container in accordance with local disposal codes.

**CONSULT ARC TECHNICAL DEPARTMENT  
 FOR ANSWERS TO ANY QUESTIONS  
 REGARDING USE OF THIS PRODUCT**

4ZTUFN XBSSBOUZ BWBJMBCMF 8IFO TPME TFQBSBUF GSPN TZTUFN UIFSF JT OP XBSSBOUZ HJWFO FYQSFTTFE PS JNQMJFE UISPV  
 UFTUFE UP DPOGPN UP UIFTF TUBOEBSET 5FTUJOH JT QFSGPSNFE PO B SBOEPN CBTJT CZ PVS JO IPVTF BOE JOEFQFOEFOU UIJSE  
 UIF TPFM SFTQPOTJCMJUZ PG UIF CVZFS CVZFS T BHFOU PS UIF CVZFS T DVTUPNFS "3\$ BTTVNFT OP SFTQPOTJCMJUZ GPS DPW  
 (6"3"/5: 03 8"33"/5: 0' "/: ,\*/% \*4 ."%& #: "\$& 300' \$0"5"/(4 \*/\$ 03 \*54 46#4\*%"\*3\*& &913&44&% 03 \*.1-\*&% 45"56503: #: 01&3"5"0/ 0  
 \$04.&5\*\$ "11&"3"/\$& .&3\$)/5"#\*-5: "/% '\*5/&44 '03 " 1"35\*\$6-"3 163104&