

A·R·C·HITECTURAL[®]

ROOF COATINGS



MADE IN  THE USA

• **PRODUCT DATA SHEET**

HydroSHIELD[™] Standard White

• **DESCRIPTION**

HydroSHIELD[™] Standard White is an acrylic elastomeric polymer fortified with fibers. It dries by evaporation to yield a non- yellowing, water- repellent surface.

HydroSHIELD[™] Standard White is UV stable, and has exceptional abrasion resistance. A sustainable cool roof coating.

• **RECOMMENDED USES**

HydroSHIELD[™] Standard White can be applied to surfaces such as metal, masonry, wood, and over ARC primers after following preparation procedures.

• **APPLICATION**

Surface to be treated must be clean. If necessary, remove all dust, grease and loose debris before applying this product. Apply with a brush, roller, or sprayer at a rate of 1.00 gallon per 100 square feet per pass. Multiple passes may be applied at 1 gallon per 100 square feet.

• **BENEFITS**

Mildew Resistant	Non-Toxic
Flexible	Easy Clean Up
Non- Yellowing	Abrasion Resistant
Energy Saving	Prevents Rust
Waterproof	

• **TECHNICAL DATA**

EMITTANCE:	.90 ASTM C-1371
REFLECTANCE:	.78% Energy Star Listed
FLEXIBILITY:	Passed 180° Mandrel Bend Test ASTM D-822
VISCOSITY:	6,000 - 9,000 cps
WEATHERABILITY:	Passed 4000 Hours ASTM G-53
FIRE RESISTANCE:	Class "A" in Assembly
FUNGAL RESISTANCE:	Passed ASTM D-3273-73T
ELONGATION:	300% at 70° F ASTM 2370
CLEAN UP:	Biodegradable citrus cleaning products or soap and water
TENSILE:	380 psi ASTM D-2370
PERMEABILITY:	1.8 perms ASTM D-1653A
SOLIDS BY WEIGHT:	60% +/- 2% ASTM D-1644
SOLIDS BY VOLUME:	52% +/- 2% ASTM D-2697
VOC:	<50 grams per liter
WEIGHT:	11.67 lbs. per gallon +/- 5%

- **CAUTION:** *High humidity requires a longer time for water-based coatings to form a film that is rain resistant.*

Avoid breathing fumes and prolonged contact with skin. Do not ingest. Keep containers covered when not in use. When using, provide proper ventilation. Dispose of product and container in accordance with local disposal codes.

**CONSULT ARC TECHNICAL DEPARTMENT
FOR ANSWERS TO ANY QUESTIONS
REGARDING USE OF THIS PRODUCT**

System warranty available. When sold separate from system there is no warranty given, expressed or implied, through the values or statements made here, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by our in house and independent third party labs in order to obtain approval and/or classification. Acceptance, purchase and selection of these products are the sole responsibility of the buyer, buyer's agent, or the buyer's customer. ARC assumes no responsibility for coverage, performance, or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER GUARANTY OR WARRANTY OF ANY KIND IS MADE BY ACE ROOF COATINGS, INC. OR ITS SUBSIDIARIES, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING COSMETIC APPEARANCE, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.