

A·R·C·HITECTURAL[®]

ROOF COATINGS



MADE IN



THE USA

• **PRODUCT DATA SHEET**

HydroSHIELD™ T₂S ACTIVATOR

DESCRIPTION

HydroSHIELD™ T2S Activator is designed to be used with HydroSHIELD™ T2S products. This activator solution must be mixed before use. Be sure to stir solids off bottom of container before use. HydroSHIELD™ T2S Activator is environmentally friendly ~ non pollutant.

RECOMMENDED USES

HydroSHIELD™ T2S Activator is exclusively designed to draw water out of HydroSHIELD™ T2S products and treats moisture on roof with antifreeze to eliminate cold wall blisters.

APPLICATION

HydroSHIELD™ T2S Activator is to be spray applied only. Set sprayer on mist and apply over HydroSHIELD™ coatings within 3 minutes of coating being applied for best results. Multiple coating layers can be applied by sprayer with activator misted over coating. It is recommended to spray apply both coatings and activator. Gently apply using low pressure, multiple coats of HydroSHIELD™ T2S over first coat, coating each pass of coating with activator, rinse in between if not raining.

BENEFITS

Increases Productivity

Non-Toxic

Easy Clean Up

Extends Workday

Makes HydroSHIELD™

T2S coatings rain

resistant in 5 minutes!

TECHNICAL DATA

COLOR:	Clear
VISCOSITY:	500cps +/- 5%
FUNGAL RESISTANCE:	Passed ASTM D-3273-73T
CLEAN UP:	Soap and water
SOLIDS BY WEIGHT:	9% +/- 5% ASTM D- 1644
SOLIDS BY VOLUME:	7% +/- 5% ASTM D- 2697
VOC:	<50 grams per liter
WEIGHT:	8.4 lbs. per gallon +/- 5%
COVERAGE:	1:11 activator:coating ratio

NOTE: Flush spray hose thoroughly, at least 5 gallons of clean water and then spray all metal moving parts with WD-40.

CAUTION: DO NOT SWALLOW THIS PRODUCT!

T2S "Technology - Two Step" permits ARC coating to be applied over moisture, damp or dew surfaces without permitting cold wall blistering as well as develops a rain/wash-off resistance within 5 minutes. Second pass of ARC coating can be applied in less than 2 hours, if no rain, rinse gently.

System warranty available. When sold separate from system there is no warranty given, expressed or implied, through the values or statements made here, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by our in house and independent third party labs in order to obtain approval and/or classification. Acceptance, purchase and selection of these products are the sole responsibility of the buyer, buyer's agent, or the buyer's customer. ARC assumes no responsibility for coverage, performance, or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER GUARANTY OR WARRANTY OF ANY KIND IS MADE BY ACE ROOF COATINGS, INC. OR ITS SUBSIDIARIES, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING COSMETIC APPEARANCE, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.