

A·R·C·HITECTURAL[®]

ROOF COATINGS



MADE IN  THE USA

• **PRODUCT DATA SHEET**

ULTRA 7000

• **DESCRIPTION**

ULTRA 7000 is an acrylic elastomeric roof coating fortified with silicone. It dries by evaporation to yield a non- yellowing, water- repellent surface. ULTRA 7000 is UV stable, and has exceptional abrasion resistance. A sustainable cool roof coating.

• **RECOMMENDED USES**

ULTRA 7000 can be applied to roof surfaces such as metal, wood, rolled roofing, BUR, PUF, smooth and granular roofing surfaces, masonry, and over ARC primers after following preparation procedures.

• **APPLICATION**

Roof surface to be coated must be clean. If necessary, remove all dust, grease and loose debris before applying Ultra 7000. Apply with a brush, roller, or sprayer at a rate of 1.00 gallon per 100 square feet per pass. Multiple passes may be applied at 1 gallon per 100 square feet.

• **BENEFITS**

Fungus Resistant	Non-Toxic
Flexible	Easy Clean Up
Non- Yellowing	Abrasion Resistant
Energy Saving	Waterproof
Nano-processed	



• **TECHNICAL DATA**

EMITTANCE:	.90 ASTM C-1371
REFLECTANCE:	.78 ASTM C-1549
SOLAR REFLECTANCE:	.97 ASTM E1980-01
FLEXIBILITY:	Passed 180° Mandrel Bend Test
CONSISTENCY:	Brush, Spray, or Roller
FLAMMABILITY:	N/A - Water-based
ELONGATION:	Up to 700% ASTM D-2370
CLEAN UP:	Soap and warm water
FUNGUS RESISTANCE:	No Growth ASTM G21
DRY TIME:	2-4 hours above 70° F @ 50% relative humidity
FULL CURE:	24-48 hours above 70° F @ 50% relative humidity
TENSILE:	Up to 225 ASTM D-2370
PERMEABILITY:	3.4 ASTM D-1653A
SOLIDS BY WEIGHT:	64% minimum
VOC:	<50 grams/liter
WEIGHT:	11.5 lbs. per gallon +/- 5%
MIL THICKNESS:	Recommended 24+ dry mils

CAUTION: High humidity requires a longer time for water-based coatings to form a film that is rain resistant.

- Avoid breathing fumes and prolonged contact with skin. Do not ingest. Keep containers covered when not in use. When using, provide proper ventilation. Dispose of product and container in accordance with local disposal codes.

**CONSULT ARC TECHNICAL DEPARTMENT
FOR ANSWERS TO ANY QUESTIONS
REGARDING USE OF THIS PRODUCT**

System warranty available. When sold separate from system there is no warranty given, expressed or implied, through the values or statements made here, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by our in house and independent third party labs in order to obtain approval and/or classification. Acceptance, purchase and selection of these products are the sole responsibility of the buyer, buyer's agent, or the buyer's customer. ARC assumes no responsibility for coverage, performance, or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER GUARANTY OR WARRANTY OF ANY KIND IS MADE BY ACE ROOF COATINGS, INC. OR ITS SUBSIDIARIES, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING COSMETIC APPEARANCE, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.