A·R·C·HITECTURAL®







PRODUCT DATA SHEET

LIQUID TPO® BIO REDUCER

DESCRIPTION

Liquid TPO* BIO Reducer is used to reduce the viscosity of all Liquid TPO* BIO based products. It is also used to clean up spills and equipment after use of Liquid TPO* BIO products.

RECOMMENDED USES

Liquid TPO* BIO Reducer is paddled into Liquid TPO* BIO products to reduce viscosity at a rate of 1 pint per 5 gallons until desired viscosity is reached. Do not exceed 1 gallon per 5 gallons of Liquid TPO* BIO product. Use to flush out spray hoses, spray gun, and clean tips as well as store brushes and rollers for reuse. May be used to clean up spilled product.

HANDLING

Use industrial chemical resistant gloves when using this product. Use a face mask and eye protection. Work with Liquid TPO* BIO Reducer outside where proper ventilation is available.

BENEFITS

Cleans Tools/Equipment
Dissolves Liquid TPO* BIO Products
Acts as a Drying Agent
Reduced odor
USDA BIOPREFERRED

TECHNICAL DATA

AROMATIC CONTENT: >99% ASTM D-1319

SPECIFIC GRAVITY: 15.6° C/15.6° C ASTM D-4052

value 0.874

COLOR: Clear ASTM D-156

FIRE RATING: Flammable ASTM D-56

°C value 46

VOC: >500

NEVER SMOKE WHEN USING CLEANING SOLVENT.

AVOID STATIC ELECTRICITY. GROUND EQUIPMENT.

Avoid breathing fumes and prolonged contact with skin. Do not ingest.
 Keep containers covered when not in use. When using, provide proper ventilation. Dispose of product and container in accordance with local disposal codes.

CONSULT ARC TECHNICAL DEPARTMENT FOR ANSWERS TO ANY QUESTIONS REGARDING USE OF THIS PRODUCT



CAN BE MADE WITH RECOVERED MATERIALS UPON REQUEST.

System warranty available. When sold separate from system there is no warranty given, expressed or implied, through the values or statements made here, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by our in house and independent third party labs in order to obtain approval and/or classification. Acceptance, purchase and selection of these products are the sole responsibility of the buyer, buyer's eagent, or the buyer's customer. ARC assumes no responsibility for coverage, performance, or injuries resulting from use. Liability , if any, is limited to replacement of the product. NO OTHER GUARANTY OR WARRANTY OF ANY KIND IS MADE BY ACE ROOF COATINGS, INC. OR ITS SUBSIDIARIES, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING COSMETIC APPEARANCE, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.