

A·R·C·HITECTURAL®

ROOF COATINGS



MADE IN  THE USA

• PRODUCT DATA SHEET

POND X

• DESCRIPTION

Pond X is a blend of asphalt and polymers to create a liquid rubberized weatherproofing membrane for low areas of the roof that collect water. Pond X is self-priming and self-leveling within minutes. You can torch or hot mop to Pond X the same day.

• RECOMMENDED USES

Pond X may also be used to fill voids and cracks on any asphalt or concrete surface. Use as a pitch pan filler or underneath A/C units that are hard to weatherproof. It is an excellent fast setting sealant. Pond X can also be used over BUR rolled or single-ply membranes. A putty like consistency to form bird stops or to finish tile roofing tie ends is available upon request. Use this product in fair weather and build up low areas around drains.

• APPLICATION

After mixing Part A with Part B for 30 seconds, pour into low areas of the roof. Minimal placement with a striker may be necessary. Allow Pond X to set for 45 minutes, and to cure for 90 minutes before hot mopping or torching the roofing membrane. To force cure, use an open torch up to 3 minutes. When coating over Pond X, allow Pond X to cure 72 hours, then apply ARC Stain Blocker.

• BENEFITS

| | |
|----------------------------------|--------------------------|
| Eliminates Water Pond Areas | Non-Hazardous |
| Used with Hot or Torch Materials | Color Finishes Available |
| Applied in Cold or Warm Weather | Non-Toxic |
| Self-Priming | Self-Leveling |

• TECHNICAL DATA

| | |
|---------------|---|
| RESIN TYPE: | Proprietary Polymer Asphalt |
| COVERAGE: | Over 1,000 cubic inches per Big Kit (4 gals.) |
| TENSILE: | 4,000 psi after 24 hours ASTM D-142 |
| ELONGATION: | Flexible ASTM D-412 |
| COLOR: | Black or White |
| PERMEABILITY: | 0.24 Perms ASTM E-96 |
| SOLIDS: | 93-97% +/- 2% ASTM D-1353 |
| WEIGHT: | 6-7 lbs. per gallon +/- 2% |
| VISCOSITY: | 500-1000 cps (Brookfield) Putty consistency available |
| FLASH: | None ASTM D-1310 |
| POT LIFE: | up to 4 minutes (up to 4 hours available) |
| STORAGE: | 1 year prior to activation in unopened container. Store between 40° -100° F |
| SET TIME: | Within 40-45 minutes |
| FULL CURE: | 12-24 hours |
| CLEAN UP: | Wet-soap and water; Dry-citrus cleaner |
| ADHESION: | Pass (concrete, asphalt) ASTM D-413 |
| RECOVER: | After set, can hot mop or torch |

- Avoid breathing fumes and prolonged contact with skin. Do not ingest. Keep containers covered when not in use. When using, provide proper ventilation. Dispose of product and container in accordance with local disposal codes. **THIS PRODUCT CAN FREEZE. STORE ABOVE 40° F.**

System warranty available. When sold separate from system there is no warranty given, expressed or implied, through the values or statements made here, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by our in house and independent third party labs in order to obtain approval and/or classification. Acceptance, purchase and selection of these products are the sole responsibility of the buyer, buyer's agent, or the buyer's customer. ARC assumes no responsibility for coverage, performance, or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER GUARANTY OR WARRANTY OF ANY KIND IS MADE BY ACE ROOF COATINGS, INC. OR ITS SUBSIDIARIES, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING COSMETIC APPEARANCE, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.